NINGBO LCK ELECTRONICS CO.LTD TECHNICAL DATA SHEET

PART NO.: KABL-ALARM-6x0.22

ISSUE NO. : 1

DESCRIPTION: 6C ALARM CABLE SCREENED PVC

ISSUE DATE : JULY 28.2023 CABLE CONSTRUCTION

Category Type	6C ALARM CABLE SCREENED				
Test Standard	UL1581				
1.Conductor	Material	Stranded CCA(8%)			
	Nom.O.D.(mm)	0.20×7	Up	+0.008	
			Down	-0.008	
2.Insulation	Material	PVC			
	Diameter	1.10(+/-0.13)mm×6			
Color	red,blue,	1.10(+/-0.13)mm×6 green,yellow,white,black Stranded CCA(8%) Up +0.008			
3.Drain	Material	Stranded CCA(8%)			
	Nom.O.D.(mm)	0.20×7	Up	+0.008	
			Down	-0.008	
4.Shield	Material	AL-foil			
	Color	Silver			
5.Jacket	Extemal O.D.mm	4.6(+/-0.25)mm			
	Surface	Clean,Smooth			
	Material	PVC			
	Color	WHITE			
CHARACTERISTICS	Item	Description			Standard
	1.Cond. Resistance	20°C, Conductor DC Resistance			< 16.00 Ω/100M
	2.Min.Insulation DC Resistance	20℃,Insulation DC Resistance			>200 MΩ*M
	3.Rated Volage				80V
	4.Rated Temperature				60℃







Information in this data sheet supplied to users is based on general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of the products, no warranty is given nor is to be implied with respect to such information. Users should make their own enquiries to determine the stability of products for any particular use.