NINGBO LCK ELECTRONICS CO.LTD TECHNICAL DATA SHEET						
PART NO. :KABL-COAX RG59+2x0.75 CCA/PE/100M ISSUE NO. : 2 ISSUE DATE : JULY 28,2023 CABLE CONSTRUCTION						
Category Type	V cable with power cable PE sheath RG59+2x0.75mm2					
Test Standard	UL1581,UL444.				•	
	Material		CCA(8%)		•	
1.Conductor	Nom.O.D.(mm)	1X0.81	Up Down	+0.010 -0.010		
2.Dielectic	Material		FPE		1	
	Diameter	3.7+/-0.18)mm		า]	
Color		WHITE				
3.Shielded	Material	Copper color Aluminum				
4,Braiding:	Material		CCA(8%)			
	Size:	128*0.12mm				
5,Outer Jacket	Material	PE				
	Color	Color BLACK				
	Diameter	6.0mm+/-0.2mm				
5,Power cable	2C	RED/BLACK				
4.Conductor	Material	CCA(8%)				
	Nom.O.D.(mm)	0.20×24	Up Down	+0.008 -0.008		
5.Dielectic	Material		PE]	
	Diameter	5.4+/-0.5MM				
	Color	BLACK				
CHARACTERISTICS	Item	Description			Standard	
	1.Cond.(1) Resistance	20°C, Conductor DC Resistance			<50.50Ω/100M	
	2.Cond.(2) Resistance	20°C, Conductor DC Resistance			<20.00Ω/100M	
	3.Rated Volage				80v	
	4.Rated Temperature				80°C	
	5.Impedance(Ω)	200MHZ			75±5Ω	
	6.Capacitance(pF/m)				67(+/-5)	
	Frequency (MHz)				Attenuation (dB)+/-20%	
	5,0 10,00				<u>13</u> 14	
	200,00			28		
	400,00			29		
	800,00			40		
	1000,00				60	
* * * * * * * * * * * * * * * * * * *						

Information in this data sheet supplied to users is based on general experience and is given in good faith, but because of the many particular factors which are outside our knowledge which affect the use of the products, no warranty is given nor is to be implied with respect to such information. Users should make their own enquiries to determine the stability of products for any particular use.